



USA | UPPAbaby, 276 Weymouth Street, Rockland, MA 02370 Canada | 5514KM, 201 Wicksteed Avenue, Suite 2, Toronto, Ontario M4G 0B1 uppababy.com | 1.844.823.3132

Model 1319-ALT-CA

All rights reserved. © 2022 UPPAbaby. UPPAbaby and all associated logos are trademarks. All product specifications are correct at time of print. UPPAbaby reserves the right to change anything at any time without prior notice. Color representation is as close as print processes allow. Not all colors available at all retailers. UbMAN053-V04





Product Information	2	Using the ALTA	16
Registration	2	Booster Assembly	16
ertification	2	Active Response Headrest Adjustment	18
Lifetime Warranty	3	SECUREFit Lap Belt Positioner	19
•		Install Using Lower Anchors	21
Warnings + General Safety Information	4	Release from Lower Anchors	23
		Storing Lower Anchors	24
Child Usage Requirements	9	Use Without Lower Anchors	25
Vehicle Compatibility	10	Securing the Child	26
Overview of Vehicle Seat Belt Systems	10	. The state of	
Universal Anchorage System (UAS)	12	Additional Information	28
Vehicle Head Restraint	13	Attaching/Removing Lap Belt Positioner Cover	28
		Remove and Install Seat Cover	29
Product Overview	14	Remove and Install Headrest Cover	31
		Cup Holder Use	35
		Cleaning and Maintenance	36
Read all instructions before of this Child Restraint.	Warranty	37	
Keep these instructions for future reference.			

#### PRODUCT INFORMATION

#### REGISTRATION

Model Number:						
Manufactured Date:						
Expiration Date:						

**TAKE A MOMENT TO FILL OUT THE ABOVE INFORMATION** which can be found on the bottom of your ALTA Child Restraint



Thank you for selecting the ALTA Child Restraint from UPPAbaby. Please register your Child Restraint by filling out and sending the postage-paid registration card that came with your Child Restraint or register online at: uppababy.com/ca/register/carseat.

Child Restraints can be recalled for a variety of safety reasons. You MUST register this restraint to be reached in a recall.

For recall information, call Transport Canada's Motor Vehicle Safety Centre at 1-800-333-0371 or go online to www.tc.gc.ca/en/transport-canada.html.

#### CERTIFICATION



This child restraint system conforms to

all applicable Canadian Motor Vehicle Restraint Systems and Booster Seat Safety Regulation (RSSR) and Canadian Motor Vehicle Safety Standard (CMVSS 213) for child restraint systems and (CMVSS 213.2) for booster seats.

# WELCOME TO FAMILY

We are with you for the long haul. Register your car seat within three months to claim your Limited Lifetime Warranty.\*

Thank you for being part of the UPPAbaby family.



\*Lifetime warranty applies to UPPAbaby car seats and the original owner, within the lifetime of the product. To receive your Limited Lifetime Warranty, you MUST register within three months of purchase and provide a valid purchase receipt form an authorized UPPAbaby retailer. The "lifetime" of the product is defined as the period of use by the registrant for use with his/her children up to 10 years from date of manufacture. For complete UPPAbaby Warranty refer to page 37.

For replacement parts, service or additional questions, please contact our Customer Experience Team: uppababy.com/support | email: support@uppababy.com | 844-823-3132

#### WARNINGS + GENERAL SAFETY INFORMATION

## **MARNING**

## **DEATH OR SERIOUS INJURY CAN OCCUR**

According to accident statistics, children are statistically safer when properly restrained in the rear seating positions than in the front seating positions, whether there are airbags, advanced airbags or no airbags at all. To ensure your child's safety refer to approved seating positions on page 12 in this manual or your Vehicle's Owner Manual.

- **NEVER** leave Child Restraint unsecured in your vehicle even when it is unoccupied. In a crash, it could become a projectile and injure other vehicle occupants.
- **DO NOT** use this Child Restraint without the seat cover. Failure to do this can result in serious injury.
- Use this Child Restraint only on vehicle seats that face forward.
- **DO NOT** use on seats that face the sides or rear of the vehicle.

#### **WARNINGS + GENERAL SAFETY INFORMATION**



**NEVER** place this Child Restraint on a front seat with an airbag unless the airbag can be turned off. **DEATH OR SERIOUS INJURY** can occur. The back seat is the safest place for children 12 and under. Refer to the vehicle owner's instruction book before installing this Child Restraint in a seating position with side airbags.

- Failure to follow all warnings, product labels and instructions could result in SERIOUS INJURY or DEATH.
- **NEVER** leave child unattended.
- DO NOT use this Child Restraint system if it has been in a vehicle accident.
- Ensure that the child's head is positioned correctly within the headrest and that the shoulder belt is placed correctly over the child's shoulders.

#### **WARNINGS + GENERAL SAFETY INFORMATION**

- **DO NOT** use this Child Restraint system in a vehicle seating position where it cannot be tightly secured.
- **DO NOT** modify this restraint except as instructed in this instruction book. Minor modifications can change the way a Child Restraint performs in a crash.
- **DO NOT** leave loose objects, e.g. cups, toys, bags, umbrellas, etc., in the vehicle because they can become deadly projectiles in a crash.
- **DO NOT** take child out of this Child Restraint while the vehicle is moving.
- **DO NOT** allow children to play with this Child Restraint. It is not a toy.
- **NEVER** use any non-regulated products with this Child Restraint including any accessories, pads, or products supplied by other manufacturers, unless approved and tested by UPPAbaby. Items not tested with this restraint could injure your child.
- **DO NOT** remove or cover up any of the warning labels or other labels on this Child Restraint.

#### **WARNINGS + GENERAL SAFETY INFORMATION**

- ALWAYS check all surfaces of restraint before securing your child. In warm
  weather, Child Restraints can become very hot and may result in burns to
  your child. Park in the shade or where sun does not directly hit the Child
  Restraint. Cover the Child Restraint with a sheet or blanket when not in use.
- ALWAYS properly store Lower Anchor Connectors when not in use.
- This child seat can only be used in the following classes of vehicles: multi-purpose passenger vehicles, passenger cars, or trucks.
- Check the vehicle's owner manual for more information about airbag/ Child Restraint use.
- For vehicles without a back seat, refer to your vehicle's owner manual.
- Check the vehicle belt before each use. Use only if the belt is tightened properly and securely.
- **DO NOT** use a Child Restraint with damaged or missing parts.
- Read all instructions for additional warnings.

#### **WARNINGS + GENERAL SAFETY INFORMATION**

- **DO NOT** use only the lap belt when using this seat.
- The shoulder belt must always be adjusted snugly across the child's chest.
- **NEVER** place the shoulder belt under the child's arms.
- Failure to follow these warnings could cause serious injury or death to your child.
- **NEVER** use this Child Restraint on an aircraft. This restraint is **NOT** certified for use in aircraft, because aircraft do not have shoulder belts.

## **CHILD USAGE REQUIREMENTS**

This Child Restraint is for use by children who meet BOTH requirements below:



**WEIGHT:** 18.1 kg - 45.4 kg (40 - 100 lbs)

**HEIGHT:** 96.5 - 144.8 cm (38 - 57 in)

- **DO NOT** use this booster beyond the expiration date or if the child outgrows either the weight or height requirements.
- This booster is **NOT** for use with children who weigh less than 18.1 kg (40 lbs).
- Use only the vehicle's lap and shoulder belt system when restraining the child in this booster.
- IMPORTANT: This product is NOT to be used without a backrest, and the backrest should never be separated from the base.

## **VEHICLE COMPATIBILITY** – Overview of Vehicle Seat Belt Systems

## **AWARNING**

## DEATH OR SERIOUS INJURY CAN OCCUR

**CHECK YOUR VEHICLE INSTRUCTION BOOK** for information regarding your vehicle seat belt system(s).

Not all vehicle seat belts work with this Child Restraint.

- Use only the vehicle's lap and shoulder belt system when restraining the child in this Child Restraint.
- **DO NOT** use this Child Restraint with the following seat belt systems:








Motorized (Automatic)


**NOTE:** Refer to your vehicle's owner manual for information regarding booster use with vehicle seats that have switchable retractors or inflatable seat belts


## **VEHICLE COMPATIBILITY** – Overview of Vehicle Seat Belt Systems

## PLEASE READ THE FOLLOWING INFORMATION BEFORE INSTALLING THIS CHILD RESTRAINT! Check Your Vehicle's Owner Manual

Vehicle seat belts differ from vehicle to vehicle. This booster is compatible with most vehicle seat belt systems and can ONLY be used with three-point (lap-shoulder) vehicle seat belts.











This Child Restraint can only be installed on vehicle seats that face forward.

**DO NOT** install in seats that face to the sides or rear of the vehicle

## **VEHICLE COMPATIBILITY** — Universal Anchorage System (UAS)

The universal anchorage system helps to anchor the booster seat in the car for stability and to prevent it from becoming a projectile when not occupied in the event of a crash.


This booster can be installed with lap shoulder belts in a vehicle that contains lower anchors. You must use the lap-shoulder belt to properly secure your child. The lower anchors must be standard spacing 28 cm (11 in). Check your vehicle's owner manual to determine lower anchor compatible seating positions.

When not in use, the lower anchor connectors must be properly secured in the base of the booster.




## **VEHICLE COMPATIBILITY** – Vehicle Head Restraint

The back of the booster seat MUST fit tightly against the back of the vehicle seat. If the vehicle head restraint cannot be adjusted or removed, a different seating position or different booster seat should be used.



**IMPORTANT:** If you remove your vehicle head restraint, be sure to stow in a secure place; check your vehicle's owner manual. Replace the head restraint when the booster is removed from the vehicle seat.




## PRODUCT OVERVIEW

0

14



## PRODUCT OVERVIEW




- A SECUREFit Shoulder Belt Guide
- **B** Upper Seat Cover
- **C** Side Impact Pods
- **D** Armrests
- **E** Cup Holder Attachment
- F Lower Seat Cover
- **G** SECUREFit Lap Belt Guide
- **H** Lower Anchor Connector Release/ Red to Green Indicator
- I Rigid Lower Anchor Connect
- J Energy Response Headrest
- **K** SECUREFit Lap Belt Positioner
- L Lap Belt Positioner Cover
- M Lower Anchor Release Handle


## **USING THE ALTA** – Booster Assembly

**IMPORTANT:** This product is **NOT** to be used without a backrest, and the backrest should **NEVER** be separated from the base.

- 1 Lay the Booster Seat Bottom on floor facing up.
- 2 Attach the Backrest to the Booster Seat Bottom, by hooking over the seat bar hinge on the seat bottom as shown.
- **3** Rotate the Backrest up until it clicks into the full upright position and locks into place.
- 4 Tuck the Fabric Panel between the Backrest Fabric Cover and the Seat Back Frame. Be sure Fabric Panel is flat against the Seat Back Frame.



## **USING THE ALTA** – Booster Assembly



## **USING THE ALTA** – Active Response Headrest Adjustment

#### **ADJUSTING THE HEADREST**

The Headrest can be adjusted for best fit to your child and optimized protection.

**NOTE:** The headrest can be adjusted with the child in the seat.


- 1 Squeeze grey button at top of seat.
- 2 Slide headrest to desired height.

#### PROPER HEADREST HEIGHT

Proper height of the headrest and belt guides are critical for optimal performance. The Headrest should rest just above the top of the child's shoulders ensuring the shoulder belt guide is properly positioned.



**IMPORTANT:** The child's ears **MUST** be below the top of the booster headrest.



## **USING THE ALTA** – SECUREFit Lap Belt Positioner


**IMPORTANT:** The lap portion of the belt should rest on the top of the child's thighs and **NOT** across the child's abdomen.

We strongly recommend using the Lap Belt Positioner. The Lap Belt Positioner holds the lap part of the vehicle belt in place for proper belt positioning.

#### USING THE LAP BELT POSITIONER

Hook the red Lap Belt Positioner over the Vehicle Lap Belt as shown.

**NOTE:** Adjust the Lap Belt Positioner as needed - See the ADJUSTING THE LAP BELT POSITIONER section for more details (page 20).




## **USING THE ALTA** – SECUREFit Lap Belt Positioner

#### ADJUSTING THE LAP BELT POSITIONER

**NOTE:** You may have to open the Lap Belt Positioner Soft Cover to access the buckle and strap.

- 1 Pull down on the strap to tighten.
- 2 Pull up on the bottom of the buckle to loosen.
- 3 Adjust the Lap Belt Positioner so that the vehicle lap belt lies flat and snug across the child's upper thighs and not above.






**IMPORTANT:** The lap portion of the vehicle belt **MUST NOT** rest on the child's abdomen.

## **USING THE ALTA** – Install Using Lower Anchors

Lower Anchors can be used to prevent the booster from becoming a projectile in the car when not in use. The Lower Anchor system does not restrain your child. You must use the lap-shoulder belt to properly secure your child. Always refer to your vehicle's owner manual to determine if your vehicle is equipped with Lower Anchors and in what seating positions.

#### TO INSTALL USING LOWER ANCHORS

- To release the Rigid Lower Anchors Connectors, pull the Lower Anchors Release handle located at the front of the seat to expose from the storage housing.
- 2 Rotate the Rigid Lower Anchors Connectors 180-degrees until they are pointing toward the Lower Anchors in the vehicle






## **USING THE ALTA** – Install Using Lower Anchors

**NOTE:** Before installing the booster, pull the Rigid Lower Anchor Connectors to ensure they are fully extended from the housing.

- 3 Place the booster on the vehicle seat. Push the Rigid Lower Anchor Connectors onto BOTH Lower Anchors until you hear a click. The red to green indicators located on connectors should be green indicating a secure connection. Pull back on each connector to ensure secure.
- 4 Pull Lower Anchor Release Handle and push the booster in the seat bight until the backrest sits against the vehicle seat back



The back of the booster **MUST** fit tightly against the back of the vehicle seat, and the front of the booster **MUST NOT** hang over the front of the vehicle seat. If the vehicle head restraint cannot be adjusted or removed, a different seating position or different booster seat should be used




The Rigid Lower Anchor Connector indicators will both show **GREEN** when properly secured.

## **USING THE ALTA** – Release from Lower Anchors

#### TO RELEASE FROM LOWER ANCHORS

To release the booster from the Lower Anchors pull back on the Lower Anchor Connector Release located on the side of each Rigid Lower Anchor Connector and remove the booster from the vehicle seat.





**IMPORTANT: NEVER** leave Child Restraint unsecured in your vehicle even when it is unoccupied. In a crash, it could become a projectile and injure other vehicle occupants.

## **USING THE ALTA** – Storing Lower Anchors

#### TO STORE RIGID LOWER ANCHOR CONNECTORS

- Rotate both Rigid Lower Anchor Connectors back towards seat.
- 2 While pulling the Lower Anchor Release at the front of booster, simultaneously push the Lower Anchor Housing back towards the booster until it locks into place.





**IMPORTANT: ALWAYS** properly store Rigid Lower Anchor Connectors when not in use.

## **USING THE ALTA** – Use Without Lower Anchors


#### TO INSTALL WITHOUT USING LOWER ANCHORS

With Rigid Lower Anchor Connectors stored, place the booster on the vehicle seat with the backrest flush with the vehicle seat back.

**IMPORTANT: NEVER** leave Child Restraint unsecured in your vehicle even when it is unoccupied. In a crash, it could become a projectile and injure other vehicle occupants. When not using Lower Anchor, use the vehicle lap and shoulder belt to secure the booster.



The back of the booster **MUST** fit tightly against the back of the vehicle seat, and the front of the booster **MUST NOT** hang over the front of the vehicle seat. If the vehicle head restraint cannot be adjusted or removed, a different seating position or different booster seat should be used.



## **USING THE ALTA** – Securing the Child

#### SECURING THE CHILD IN THE BOOSTER

- 1 With the booster correctly positioned in the vehicle and the Headrest in the proper position, route the Vehicle Shoulder Belt across the child's chest and through the RED LOWER BELT PATH (A), UNDER the armrest towards the Vehicle Buckle.
- 2 Buckle the Vehicle Shoulder Belt.
- 3 Slide the Vehicle Shoulder Belt into the RED SHOULDER BELT GUIDE (3) ensuring it passes completely under the Shoulder Belt Guide hook and does not fall off the child's shoulder. Remove slack from vehicle seat helt
- 4 The Vehicle Lap Belt must lie flat and snug across the child's upper thighs. We strongly recommend using the Lap Belt Positioner. Adjust the **RED LAP BELT POSITIONER ©** such that when you route the lap belt under it, the lap belt sits flat across the child's upper thighs and not above.





**IMPORTANT:** The child's ears **MUST** be below the top of the booster headrest.


**IMPORTANT:** the lap and shoulder belt must route under the armrests

## **USING THE ALTA** – Securing the Child

## REMOVING VEHICLE SEAT BELT

- Grasp vehicle belt on both ends of RED SHOULDER BELT GUIDE.
- Keeping vehicle belt completely flat, pull side to side under the small curve of the RED SHOULDER BELT GUIDE.
- **3** Continuing to pull side to side until the vehicle belt is released






 $\sim$  26

## Attaching/Removing Lap Belt Positioner Cover

- Position the Soft Cover and the Lap Belt Positioner as shown. Insert both tabs on the Soft Cover into the cutout in the Seat Cover.
- **2** Fold the Lap Belt Positioner forward onto the Soft Cover.
- **3** Wrap the Soft Cover over and around the Lap Belt Positioner.
- **4** Secure the Soft Cover with the hook and loop closure.





### Remove and Install Seat Cover

The Seat Cover can be removed for cleaning - See the CLEANING AND MAINTENANCE section (page 36) for more details.

#### TO REMOVE THE SEAT COVER

- 1 Locate the pull tab for the Seat Cover zipper. Unzip the zipper to release the Seat Cover from the outside edge of the Booster.
- **2** Pull to release both snap buttons at the back of the Seat Cover.






## Remove and Install Seat Cover

- **3** Pull the back of the Seat Cover out from behind the Headrest.
- **4** Pull the Seat Cover over the Lap Belt Positioner and remove from the booster.

#### TO INSTALL THE SEAT COVER

- 1 Place the Seat Cover on the Booster.
- 2 Pull the Lap Belt Positioner through the slot in the Seat Cover.
- **3** Repeat the steps used to remove the Seat Cover in reverse order.




## Remove and Install Headrest Cover

The Headrest Cover can be removed for cleaning - See the CLEANING AND MAINTENANCE section (page 36) for more details.

#### TO REMOVE THE HEADREST COVER

- 1 Pull on the lower edge of the Headrest cover to remove the fabric from the slot that runs around the outside of the Booster. Continue up the side of the booster, pulling the fabric away from the side bolsters and red Shoulder Belt Guide. Repeat for the other side.
- 2 Pull the fabric out of the slot in the top of the Booster. Pull the fabric forward and down making sure both elastic straps are pulled forward through the cutouts in the foam.




## Remove and Install Headrest Cover

- **3** Continue to pull the top of the Headrest Cover fabric down to release the elastic straps from both of the plastic hooks in the Booster.
- 4 Remove the Headrest Cover from the Booster.

#### TO INSTALL THE HEADREST

1 Locate the fabric key stored inside the pocket in the seat fabric.


**NOTE:** If the Seat Cover has not been removed, you will need to unzip the Seat Cover to access this fabric key storage pocket.






## Remove and Install Headrest Cover


- 2 Hook the elastic straps on the Headrest Cover around both of the plastic hooks located at the top of the Booster seat back. Pull both elastic straps up and through the cutouts in the foam.
- **3** Use the fabric key to push the top of the Headrest Cover into the slot at the top of the Booster.





### Remove and Install Headrest Cover

- **4** Push the Headrest Cover into the slot on the outside of the side bolster using the fabric key. Repeat for the other side.
- 5 Push the Headrest Cover into the slot on the side of the Booster using the fabric key. Repeat for the other side.
- 6 Press the Headrest into slot under the RED SHOULDER BELT GUIDE.
- 7 Continue to push the Headrest behind the Shoulder Belt Guide using the fabric key. Double check that the Headrest is tucked completely outside of the Shoulder Belt Guide. Repeat for the other side.
- **8** Store the fabric key inside the pocket in the Seat fabric.



## Cup Holder Use


#### TO ATTACH THE CUP HOLDER

Push cup holder stem into designated slot in side of the booster armrest.

#### TO REMOVE THE CUP HOLDER

Pull firmly.

**NOTE:** Cup holder can be installed on either side of booster.



⚠ WARNING: DO NOT place glass, metal containers or hard sharp objects in cup holder as they could become a projectile in a crash and cause serious injury.

**NEVER** put a hot liquid in the cup holder.

#### **CLEANING AND MAINTENANCE**

**CLEANING FABRICS** - Fabrics include: seat, headrest and lap belt positioner covers







Machine wash in cold water on gentle cycle with mild detergent. **DO NOT** bleach.

Dry flat and away from direct sunlight before re-use or storage.

**DO NOT** iron or dry clean.

#### CLEANING LAP BELT POSITIONER WEBBING





Air dry completely before re-use or storage.

Spot clean using warm water with mild detergent. **DO NOT** bleach.

#### CLEANING PLASTIC





Spot clean using warm water with mild detergent.

Towel dry completely before re-use or storage.

**CLEANING LOWER ANCHOR CONNECTORS** - Anchors should fasten with a "click". If not, rinse under warm running water. **DO NOT** use detergents or lubricants.

#### WARRANTY



Welcome to the UPPAbaby family! We are with you for the long haul. Register your car seat within three months to claim your Limited Lifetime Warranty\*.

#### Register your product at: uppababy.com/register

\*Lifetime warranty applies to UPPAbaby car seats and only the original owner, within the lifetime of the product. To receive your Limited Lifetime Warranty, you MUST register your car seat within three months of purchase and provide a valid purchase receipt from an authorized UPPAbaby retailer. The "lifetime" of the product is defined as the period of use by the registrant for use with his/her children up to 10 years from date of manufacture.

Your UPPAbaby product is warranted to be free from any manufacturing defects for a period of 2 years from the date of purchase under normal use and in compliance with the operating instructions.

This warranty is not transferable and extends only to the original retail purchaser and is only valid when supplied with proof of purchase from an authorized retailer. Proof of purchase must be retained for this warranty.

The warranty is valid only in the original country of purchase. This warranty is subject to the conditions set forth by country in which the items were purchased. Conditions may vary. UPPAbaby will not ship replacement or repair parts out of the country of purchase.

UPPAbaby will provide replacement parts or conduct repairs as determined fitting by the company. UPPAbaby reserves the right to exchange item with a replacement part. Some parts may be replaced with newer model parts as the product is improved over time.

#### WARRANTY

This warranty does not cover:

- Defects caused by misuse or poor maintenance. (Please refer to the product instruction manual for guidance on item use and maintenance).
- Damage caused by improper installation of UPPAbaby parts and/or accessories. (Please refer to product instruction booklet for guidance on item assembly and use).
- Damage caused by corrosion mold or rust due to poor maintenance, service or storage.
- Damage resulting from normal wear and tear.
- Damage or degradation caused by the sun, sweat, detergents, damp storage conditions or frequent washings.
- Repairs or modifications carried out by a third party.
- · Product purchased from an unauthorized retailer. (Approved retailers are listed on our website uppababy.com).
- Second owners and users other than the registrant.
- Damage resulting from airline shipping and handling.
- Products Involved in an accident.

UPPAbaby reserves the right to determine if warranty terms and conditions have been met.

For warranty service: In the US and CA please contact UPPAbaby customer service (844) 823-3132 and visit uppababy. com/support to send an email.